



5/8" SPIRAL BALANCE MADE FOR NON-TILT RESIDENTIAL & COMMERCIAL WINDOWS.

SMOOTH, UNIFORM OPERATING FORCE
*THIS TECHNOLOGY PROVIDES CONSISTENT, UNIFORM
OPERATION THROUGHOUT THE FULL TRAVEL RANGE OF THE
SASH*

BROAD ADJUSTABLE WEIGHT RANGES
*REDUCE INVENTORY REQUIREMENTS
FINE TUNE WINDOW PERFORMANCE
FIELD ADJUSTABLE*

PERFORMANCE TO AAMA CLASS 2
BALANCE PROVIDES A MINIMUM OF 40% LIFT ASSISTANCE

SPRINGS BY CALDWELL
*DELIVERS HIGH QUALITY, CONSISTENT
PERFORMANCE*

LASER WELDED ALUMINUM TUBES
PROVIDE STRUCTURAL STRENGTH AND DURABILITY

**WIDE RANGE OF HARDWARE OPTIONS
FOR SASH ATTACHMENT**
*COMPATIBLE WITH A WIDE VARIETY OF
CALDWELL BRACKETS AND CLIPS
EASILY UTILIZED IN ALUMINUM AND WOOD
WINDOW APPLICATIONS*



**WEIGHT RANGES: 4 - 40 LBS
LENGTHS: 7 - 51 INCHES
AAMA 902-07 CLASS 2
VERIFIED COMPONENT**



MAXIMUM EXTENDED LENGTH = 2 X TUBE LENGTH
 MINIMUM RETRACTED LENGTH = TUBE LENGTH + 1 1/8"

SPIREX® WEIGHT CAPACITY CHART

TUBE LENGTH (INCHES)	SASH WEIGHTS SUPPORTED (LBS)
7	4 - 24
8	4 - 25
9 - 14	4 - 26
15 - 16	4 - 28
17	4 - 40
18 - 22	6 - 40
23 - 32	7 - 40
33 - 45	12 - 40
46 - 47	14 - 40
48 - 49	16 - 40
50 - 51	18 - 40

HOW TO ORDER:

1. Determine your sash weight and tube length needed
2. Consult with Customer Service for tensioning charts and further ordering instructions.